## Can-am. MAVERICK X3 DS TURBO

## **HIGHLIGHTS**

DEFIANT	Trademark Can-Am DNA with next generation design Low seating position Ergo-Lok cockpit with four-way adjustable seats
POWERFUL	120 hp turbocharged Rotax* ACE engine     Advanced airflow dynamics     QRS-X transmission
PRECISE	<ul> <li>TTX suspension with industry leading travel</li> <li>Ultra efficient and lightweight chassis</li> <li>Sharpest handling features</li> </ul>
PLATFORM FEATURES	• 64 in. wide • 102 in. wheelbase • 14 in. of ground clearance • High torque Dynamic Power Steering (DPS™) • 20 in. suspension travel • FOX† 2.5 PODIUM† QS3 piggyback shocks • 14 in. aluminum wheels • 28 in. Maxxis† Bighorn 2.0† tires • 4.5 in. digital display with keypad • Rear tow hook



1,481 lb (671.9 kg)

Octane Blue / TURBO

ENGINE	TURBO
Туре	120 hp, Rotax ACE (Advanced Combustion Efficiency)
	900 cc turbocharged triple-cylinder engine, liquid cooled
	and high-perfomance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™)
	with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT with high-airflow,
	L/H/N/R/P
Drive Train	Selectable 2WD/4WD
	with Visco-Lok† auto-locking front differential
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS)

## SUSPENSIONS

Rear

Front Suspension	Double A-arm with sway bar/20 in. (50.8 cm) travel
Front Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar/20 in. (50.8 cm) travel
Rear Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment and bottom-out control
TIRES & WHEELS	
Front Tires	Maxxis Bighorn 2.0 28 x 9 x 14 in. (71.1 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 28 x 11 x 14 in. (71.1 x 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum
BRAKES	
Front	Dual 262 mm ventilated disc brakes
	with hydraulic twin-piston calipers

Dual 248 mm ventilated disc brakes

with hydraulic twin-piston calipers

## DIMENSIONS & CAPACITIES

Estimated Dry Weight

Chassis/Cage	Dual-phase 980 steel
LxWxH	132 x 64 x 65.4 in. (335.3 x 162.5 x 166.1 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	14 in. (35.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)
Fuel Capacity	10.5 gal (40 L)
FEATURES	
Gauge	4.5 in. (11.4 cm) wide digital display with keypad:
	Speedometer, tachometer, odometer, trips and hour
	meters, fuel, gear position, SPORT/ECO™ mode, seat belt
	and 4 x 4 indicator, front and rear diff. lock indicators,
	diagnostics, clock, battery voltage, engine temperature, DPS mode
Instrumentation	Lighter type DC outlet in central console
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlights and tail lights
Winch	N/A
Protection	Integrated front bumper
	Quarter-doors
	HMWPE full skid plate
	Rear tow hook
WARRANTY	
Factory Warranty	2 years BRP limited warranty

